

	G max.		
	1.65 _0.25		
ØF max.			

NO.	MASSE / DIMENSIO	
A	5/8-24NEF-2A	
B1	6.6	
B2	-	
С	14.2	
D	2.8	
Е	53	
F	21.8	
G	16.2	

ſ	C		
ĺ		B	

Note: Due to an automatic nomenclature syste may not be sequential.

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.			CUSTOMER
Material Specification:		01E10SL-3P	
Shell Material: Aluminium allov		Cable connecting plug Endbell with clamp and bushing Solder Cup / Pin / Layout: 10SL-3	
Shell Plating: Olive drab chromate coating over cadmium plating	Engineered for life		
Insulator Material: Neoprene	D - 71384 Weinstach/Germany Solder Cup / Pin / L		
Contact Material: Copper alloy	© All rights reserved. Reproduction or issue to third in any form wholever is only penalted with written authorization of ITT Cannon 1/1 space 1/1 spac		ion
Contact Plating: Hard silver			3. Feb 11

NO.	BESCHREIBUNG / DESCRIPTION	
1	ISOLIERKÖRPER STIFT / INSULATOR PIN	
3	DICHTKÖRPER / GROMMET	
4	ENDRING / ENDRING	
5	KONTAKTSTIFT/ CONTACT PIN	
8	DOSENGEHÄUSE / SHELL	
12	ENDGEHÄUSE / ENDBELL	