


NO.	MASSE / DIMENSION
A	40.5
B	1 3/8-18UNEF-2B
C	1 1/4-18NEF-2A
D	37.7

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

**ITT**  
 description CA3106E22-27P-F42  
 Plug, straight  
 without Endbell  
 Solder Cup / Pin / Layout: 22-27  
 Engineered for life  
 ITT CANADA CORP.  
 61-17300 Wrentham, Ontario  
 © All rights reserved. Reproduction or issue in third in any form  
 whatever is only permitted with written authorization of ITT Cannon  
 page 1/1  
 revision 302.8, Feb 11