




| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 28.8              |
| B   | 7/8-20UNEF-2B     |
| C1  | 9.1               |
| C2  | -                 |
| D   | 55                |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 12  | ENDGEHÄUSE / ENDBELL                    |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification:   |
|---|
| Shell Material: Aluminium alloy                                 |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene                                    |
| Contact Material: Copper alloy                                  |
| Contact Plating: Hard silver                                    |

|  |   |  |
|--|---|--|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  |   | drawing for<br>CUSTOMER  |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT GERMANY GmbH<br/>D - 71334 Weinstadt/Germany</small> | description CA3106E14S-9S<br>Plug, straight<br>Endbell with clamp and bushing<br>Solder Cup / Socket / Layout: 14S-9  |  |
|  | <small>© All rights reserved. Reproduction or issue to third in any form<br/>         whatever is only permitted with written authorization of ITT Cannon</small> |  page 1/1<br>revision 302.8, Feb 11 |