



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 34.1 |
| B | 1 1/8-18NEF-2B |
| C1 | 14.3 |
| C2 | - |
| D | 68 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 12 | ENDGEHÄUSE / ENDBELL |



| |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene |
| Contact Material: Copper alloy |
| Contact Plating: Hard silver |

| | | | |
|--|--------------------------|------------------------------------|--|
| all dimensions are in mm | | drawing for | |
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | CUSTOMER | |
|  ITT <i>Engineered for life</i> <small>ITT CANON GmbH</small> <small>D - 71324 Vöhringen/Germany</small> | description MS3106F18-9S | | |
| | Plug, straight | | |
| Shortened light-weight endbell without cable clamp | | Solder Cup / Socket / Layout: 18-9 | |
| <small>© All rights reserved. Reproduction or issue in any form whatever is only permitted with written authorization of ITT Cannon</small> | | <small>page</small> 1/1 | <small>revision</small> 302.8, Feb 11 |