



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 34.2 |
| B | 19 |
| C | 4 |
| D | 33.8 |
| E | 29 |
| F | 29.4 |
| G | 38 |
| H | 3.2 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| | |
|-------------------------|--|
| Material Specification: | |
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate over cadmium plating |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

| | | |
|---|--|-------------------------|
| all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | drawing for CUSTOMER |
| ITT <i>Engineered for life</i> <small>ITT DANZON GmbH D-7380 Heppenheim</small> | description CA3102E20-33S-B Box mounting receptacle | |
| | Solder Cup / Socket / Layout: 20-33 | |
| © All rights reserved. Reproduction or issue to third in any form without prior written authorization of ITT Cannon | page 1/1 | revision 382.12, Apr 11 |