



NO.	MASSE / DIMENSIO	
Α	1 1/8-18NEF-2A	
В	16.7	
С	1-20UNEF-2A	
D	9.5	
Е	19	
F	4	
G	54	
н	27	
1	35	
к	3.1	

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
8	DOSENGEHÄUSE / SHELL
14	F-ENDGEHÄUSE / F-ENDBELL



	Note: Due to an automatic nomenclature system, numbers generated may not be sequential. Notiz: Durch ein automatisches Benennungssystem können		all dimensions are in mm	drawing for
			Dimensions without tolerance indi	cations are general tolerances in acc. with DIN7168m CUSTOMER
	Nummerierungen entstehen, die nicht fortlaufend sind.		*	description CA3100F18-4P-F80
	Material Specification:		│ 🍑 ITT	Wall mounting receptacle
	Shell Material: Aluminium alloy	nting	Engineered for life	Endbell for flex tube
	Shell Plating: Olive drab chromate coating over cadmium plating			
	Insulator Material: Neoprene		ITT CANNON GmbH D - 71384 Weinstadt/Germany	AWG Crimp / Pin / Layout: 18-4
	Contact Material: Copper alloy		© All rights reserved, Reproduction or	issue to third in any form page revision strategies of ITT Cannon 302 8. Feb 11
	Contact Plating: Hard silver		wholever is only permitted with written or	uthorizotion of ITT Connon 1/1 302 8. Feb 11