


NO.	MASSE / DIMENSION
A	37.4
B	1 1/4-18UNEF-2B
C	1 1/8-18NEF-2A
D	37.7

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm		drawing for	
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		CUSTOMER	
 ITT <i>Engineered for life</i> <small>ITT CANADON GmbH</small> <small>01-71504 Weensriederweg</small>	description CA3106E20-22P-F42		
	Plug, straight without Endbell Solder Cup / Pin / Layout: 20-22		
<small>© All rights reserved. Reproduction or issue to third in any form without prior written authorization of ITT Cannon</small>	<small>page 1/1</small>	<small>revision 302.8, Feb 11</small>	