



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 34,1 |
| B | 1 1/8-18NEF-2A |
| C | 18,4 |
| D | 53 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 5 | KONTAKTSTIFT / CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 20 | KURZES ENDGEHÄUSE / SHORT ENDBELL |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| | |
|-------------------------|--|
| Material Specification: | |
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate coating over cadmium plating |
| Insulator Material: | Neoprene |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

| all dimensions are in mm | | drawing for |
|--|---|------------------------------------|
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | CUSTOMER |
|  ITT Engineered for life <small>ITT CANNON GmbH D-71364 Heppenheim/Germany</small> | description CA3106R18-1PX-F80 Plug, straight Shortened light-weight endbell without cable clamp AWG Crimp / Pin / Layout: 18-1 | |
| | <small>© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon</small> | page 1/1 revision 302.8, Feb 11 |