


NO.	MASSE / DIMENSION
A	50.2
B	1 3/4-18UNS-2B
C	1 5/8-18NEF-2A
D	39.3

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm

Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



Engineered for life
 ITT CANADA CORP.
 61-17300, Wiesbaden, Germany

description CA3106E28-11P-F42
 Plug, straight
 without Endbell
 Solder Cup / Pin / Layout: 28-11

© All rights reserved. Reproduction or issue in any form
 whatever is only permitted with written authorization of ITT Cannon



page 1/1
 revision 302.8, Feb 11