


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 37.4              |
| B   | 19                |
| C   | 4                 |
| D   | 33.8              |
| E   | 32.2              |
| F   | 31.8              |
| G   | 41                |
| H   | 3.2               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification:                                 |
|---|
| Shell Material: Aluminium alloy                         |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere                       |
| Contact Material: Copper alloy                          |
| Contact Plating: Hard silver                            |

| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m   |             | drawing for<br>CUSTOMER                      |
|---|-------------|--|
| <br>ITT<br>Engineered for life<br>ITT CANNON GMBH<br>D-71834 Weinstadt/Germany | description | CA3102E22-2P-B-01<br>Box mounting receptacle |
|   |             | Metric Crimp / Pin / Layout: 22-2            |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon                            | page<br>1/1 | revision<br>302.12, Apr 11                   |