



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 24.1 |
| B | 5/8-24NEF-2B |
| C1 | 6.6 |
| C2 | - |
| D | 22.7 |
| E | 42 |
| F | 45 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 12 | ENDGEHÄUSE / ENDBELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Notiz: Durch ein automatisches Benennungssystem können Nummernreihen entstehen, die nicht fortlaufend sind.

| Material Specification | |
|------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate coating over cadmium plating |
| Insulator Material: | Nesprene |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7169m

drawing for
CUSTOMER



description MS3108E10SL-3S
Plug 90°
Endbell with clamp and bushing
Solder Cup / Socket / Layout: 10SL-3

© All rights reserved. Reproduction is made to fit to any form where it is only permitted with written authorization of ITT Cannon. page 1/1 revision 302.8, Feb 11