



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 24.1              |
| B   | 5/8-24NEF-2B      |
| C   | 7.7               |
| D   | 13.3              |
| E   | 15.5              |
| F   | 11.7              |
| G   | 49                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICHTKÖRPER / GROMMET                |
| 5   | KONTAKTSTIFT / CONTACT PIN           |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 13  | ENDGEHÄUSE DN / ENDBELL HEATSHRINK   |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification: _____  |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate coating over cadmium plating  |
| Insulator Material: Neoprene   |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|   |   |                        |  |
|---|---|------------------------|--|
| all dimensions are in mm  |   | drawing for            |  |
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m   |   | CUSTOMER               |  |
| <br><b>ITT</b><br>Engineered for life<br>ITT CANNON GmbH<br>D-71334 Wernau/Germany | description CA3106E10SL-4P-F183-DN  |                        |  |
|   | Plug, straight<br>Endbell for heatshrink boots<br>Solder Cup / Pin / Layout: 10SL-4 |                        |  |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon                                | page 1/1  | revision 302.8. Feb 11 |  |