


NO.	MASSE / DIMENSION
A	43.8
B	1 1/2-18UNEF-2B
C	1 3/4-18NEF-2A
D	39.3

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for CUSTOMER
 ITT <i>Engineered for life</i> <small>ITT CANADA CORP. 10000 Woodbine Ave., Unit 10 Scarborough, Ontario M1S 5T9, Canada</small>	description	CA3106E24-22P-F42
	Plug, straight without Endbell Solder Cup / Pin / Layout: 24-22	
© All rights reserved. Reproduction or issue in any form without written authorization of ITT Cannon	page 1/1	revision 302.8, Feb 11