



NO.	MASSE / DIMENSION
A	29.2
B1	9.1
B2	-
C	27.5
D	42
E	47

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING
12	ENDGEHÄUSE / ENDBELL

Note: Due to an automatic nomenclature system, numbers generated may not be sequential. Note: Durch ein automatisches Benennungssystem können Nummernungen entstehen, die nicht fortlaufend sind.	
Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate over cadmium plating
Insulator Material:	CR-Elastomere
Contact Material:	Copper alloy
Contact Plating:	Gold 0,5 µm

all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN71891		drawing for CUSTOMER
 ITT Engineered for Life ITT Power Corp. 1716 Woodway Drive	description CA3108E14S-5P-B-A176 Plug, 90° Endbell with clamp and bushing Solder Cup / Pin / Layout: 14S-5	
© All rights reserved. Reproduction or use in third party files without the prior written authorization of ITT Connect.		page 1/1 revision 392 12, Apr 11