


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 59.6              |
| B   | 22.2              |
| C   | 4                 |
| D   | 33.8              |
| E   | 52.6              |
| F   | 49.2              |
| G   | 63.5              |
| H   | 4.3               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Note: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification:                                 |
|---|
| Shell Material: Aluminium alloy                         |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere                       |
| Contact Material: Copper alloy                          |
| Contact Plating: Hard silver                            |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



description CA3102E36-10PXB-F80  
 Box mounting receptacle

Engineered for life  
 ITT CANNON GmbH  
 D-71334 Weinstadt-Gemary

AWG Crimp / Pin / Layout: 36-10

© All rights reserved. Reproduction or issue in third in any form  
 whichever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 392.12, Apr 11