



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 46.7              |
| B   | 24.05             |
| C   | 4                 |
| D   | 33.8              |
| E   | 41.4              |
| F   | 39.7              |
| G   | 50.8              |
| H   | 3.7               |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

|                         |  |
|-------------------------|--|
| Material Specification: |  |
| Shell Material:         | Aluminium alloy                          |
| Shell Plating:          | Olive drab chromate over cadmium plating |
| Insulator Material:     | CR-Elastomere                            |
| Contact Material:       | Copper alloy                             |
| Contact Plating:        | Hard silver                              |

|   |   |
|---|---|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m   | drawing for<br>CUSTOMER   |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANNON GmbH<br/>D-71834 Weinstadt/Germany</small> | description CA3102E28-21P-B-05<br>Box mounting receptacle (rear mount, through holes)<br>Solder Cup / Pin / Layout: 28-21 |
| <small>© All rights reserved. Reproduction or issue to third in any form<br/>whenever is only permitted with written authorization of ITT Cannon</small>  | page 1/1<br>revision 302.12, Apr 11   |