



NO.	MASSE / DIMENSIO
А	34.1
В	1 1/8-18NEF-2B
С	16.7
D	1-20UNEF-2A
Е	9.5
F	54

NO.	BESCHREIBUNG / DESCRIPTION			
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET			
3	DICHTKÖRPER / GROMMET			
4	ENDRING / ENDRING			
6	KONTAKTBUCHSE / CONTACT SOCKET			
7	ZYLINDERGHÄUSE / BARREL			
9	ÜBERWURFMUTTER / COUPLING NUT			
14	F-ENDGEHÄUSE / F-ENDBELL			



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.		all dimensions are in mm		drawing for
Notiz: Durch ein automatisches Benennungssystem können		Dimensions without tolerance indic	CUSTOMER	
Nummerierungen entstehen, die nicht fortlaufend sind.	ļ	<u> </u>	description CA3106F18-19S	
Material Specification:		V ITT	Plug, straight	
Shell Material: Aluminium alloy			Endbell for flex tube	
Shell Plating: Olive drab chromate coating over cadmium plating	ng	Engineered for life		
Insulator Material: Neoprene		ITT CANNON GmbH D - 71384 Weinstadt/Germany	Solder Cup / Socket / Layout: 18-1	9
Contact Material: Copper alloy Contact Plating: Hard silver		© All rights reserved, Reproduction or is	issue to third in any form page page revision and first cannon of ITT Cannon 302 8. Feb 11	on
		whotever is only permitted with written ou	. Feb 11	