


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 36.5              |
| B1  | 14.3              |
| B2  | -                 |
| C   | 68                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICKKÖRPER / GROMMET                 |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT / CONTACT PIN           |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 12  | ENDGEHÄUSE / ENDBELL                 |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

|   |
|---|
| Material Specification:                                 |
| Shell Material: Aluminium alloy                         |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere                       |
| Contact Material: Copper alloy                          |
| Contact Plating: Hard silver                            |

|   |   |                         |
|---|---|-------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7188m   |   | drawing for<br>CUSTOMER |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT CANNON GmbH<br/>D-71334 Weinstadt/Germany</small> | description CA3106E18-23P-B-F80   |                         |
|   | Plug, straight<br>Endbell with clamp and bushing<br>AWG Crimp / Pin / Layout: 18-23 |                         |
| © All rights reserved. Reproduction or issue to third in any form<br>whoever is only permitted with written authorization of ITT Cannon   | page 1/1  | revision 392 12, Apr 11 |