


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 37.4              |
| B   | 24.7              |
| C   | 23.05             |
| D   | 4                 |
| E   | 55.5              |
| F   | 31.8              |
| G   | 41                |
| H   | M4                |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 20  | KURZES ENDEGEHÄUSE/SHORT ENDBELL    |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification: |  |
|-------------------------|--|
| Shell Material:         | Aluminium alloy                          |
| Shell Plating:          | Olive drab chromate over cadmium plating |
| Insulator Material:     | CR-Elastomere                            |
| Contact Material:       | Copper alloy                             |
| Contact Plating:        | Hard silver                              |

| all dimensions are in mm   |  | drawing for     |
|--|--|-----------------|
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  |  | CUSTOMER        |
| <br>ITT<br>Engineered for life<br><small>ITT CANNON GmbH<br/>D-71334 Wessling/Germany</small>  | description  | CA3100R22-21P-B |
|  | Wall mounting receptacle<br>Shortened light-weight endbell without cable clamp<br>Solder Cup / Pin / Layout: 22-21 |                 |
| <small>© All rights reserved. Reproduction or issue to third in any form<br/>whenever is only permitted with written authorization of ITT Cannon</small> | page 1/1<br>revision 392.12, Apr 11  |                 |