



NO.	MASSE / DIMENSION
A	62.8
B	2 1/4-16UN-2B
C	2 1/8-16N-2A
D	40.9

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.
Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate coating over cadmium plating
Insulator Material: Neoprene
Contact Material: Copper alloy
Contact Plating: Hard silver

all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for CUSTOMER
 ITT <i>Engineered for life</i> <small>ITT CANON GROUP 31-17388 Wiesbaden Germany</small>		description CA3106E36-10PX-F42 Plug, straight without Endbell Solder Cup / Pin / Layout: 36-10
<small>© All rights reserved. Reproduction or issue to third in any form without prior written authorization of ITT Canon</small>		page 1/1 revision 302.8, Feb 11