


NO.	BESCHREIBUNG / DESCRIPTION	
1	ISOLIERKÖRPER STIFT / INSULATOR PIN	
5	KONTAKTSTIFT/ CONTACT PIN	
7	ZYLINDERGHÄUSE / BARREL	
9	ÜBERWURFMUTTER / COUPLING NUT	
10	DICHTRING FRONT / FRONT SEALING RING	



NO.	MASSE / DIMENSIO		
А	60.1		
в	1 7/8-16N-2A		
с	41		

ſ	<b>D</b>	Ó	
	Ĝ	<b>B</b>	
Ń			//

Note: Due to an automatic nomence may not be sequential.

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for
Notiz: Durch ein automatisches Benennungssystem können			CUSTOMER
Nummerierungen entstehen, die nicht fortlaufend sind.	>>	description CA3106E32-17PW	/B-F42
Material Specification:	🗆 💙 ІТТ	Plug, straight	5112
Shell Material: Aluminium alloy		without Endbell	
Shell Plating: Olive drab chromate over cadmium plating	Engineered for life		
Insulator Material: CR-Elastomere	ITT CANNON GmbH D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layout: 32-17	
Contact Material: Copper alloy	© All rights reserved. Reproduction or issue to third in any form whatever is only penihled with written authorization of (TT Cannon U) page 12/11 392 12		ion
Contact Plating: Hard silver	whotever is only pernitted with written ou	2. Apr 11	