



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 39.9 |
| B | 22 |
| C | 53 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 20 | KURZES ENDEGHÄUSE/SHORT ENDBELL |



| |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere |
| Contact Material: Copper alloy |
| Contact Plating: Hard silver |

| | |
|--|---|
| all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7188m | drawing for CUSTOMER |
|  ITT Engineered for life <small>ITT CANNON GmbH D-71634 Feuerbach/Germany</small> | description CA3106R20A48S-B-F80 Plug, straight Shortened light-weight endbell without cable clamp AWG Crimp / Socket / Layout: 20A48 |
| <small>© All rights reserved. Reproduction or issue to third in any form whenever is only permitted with written authorization of ITT Cannon</small> | page 1/1 revision 392.12, Apr 11 |