


NO.	MASSE / DIMENSIO
Α	37.4
В	19.8
С	1 3/16-18UNEF-2A
D	9.5
Е	23.05
F	4
G	62
Н	31.8
ı	41
к	M4

	NO.	BESCHREIBUNG / DESCRIPTION
	2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET
	3	DICHTKÖRPER / GROMMET
	4	ENDRING / ENDRING
	6	KONTAKTBUCHSE / CONTACT SOCKET
	8	DOSENGEHÄUSE / SHELL
	14	F-ENDGEHÄUSE / F-ENDBELL



Notic: Due to an automatic nomenclature system, numbers generated may not be sequential.  Notiz: Durch ein automatisches Benennungssystem können Nummerkerungen entstehen, die nicht fortlaufend sind.  Oder den automatisches Benennungssystem können (CUSTOMER)  description (CA3100F22-19S-B)		
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entsthen, die nicht fortlaufend sind.		
	Notiz: Durch ein automatisches Benennungssystem können	Dimensions without tolerance indications are general tolerances in acc. with DIN7168m CUSTOMER
	Nummenerungen entstenen, die nicht fortlaufend sind.	description CA3100F22-19S-B
Material Specification: Wall mounting receptacle	Material Specification:	Wall mounting receptacle
Shell Material: Aluminium alloy Endbell for flex tube	Shell Material: Aluminium alloy	• • •   • .
Shell Plating: Ulive drap chromate over cadmium plating     Engineered for life	Shell Plating: Olive drab chromate over cadmium plating	Engineered for life
Insulator Material: CR-Elastomere Solder Cup / Socket / Layout: 22-19	Insulator Material: CR-Elastomere	TT CANNON GmbH D-71384 Weinstadt/Germany Solder Cup / Socket / Layout: 22-19
Contact Material: Copper alloy  Contact Platino: Hard sliver  Contact Platino: Hard sliver  And the state of	Contact Material: Copper alloy	© All rights reserved. Reproduction or issue to third in any form page revision
Contact Plating: Hard silver software is only penalted with wither authorization of ITT Common 1/1/1 392.12. Apr 11	Contact Plating: Hard silver	whotever is only pennitted with written authorization of ITT Connon 1/1/1 392 12. Apr 11