



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 40.9              |
| B   | 27.6              |
| C   | 23.05             |
| D   | 4                 |
| E   | 54                |
| F   | 34.9              |
| G   | 44.5              |
| H   | M4                |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 20  | KURZES ENDEGEHÄUSE/SHORT ENDBELL    |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification: |  |
|-------------------------|--|
| Shell Material:         | Aluminium alloy                          |
| Shell Plating:          | Olive drab chromate over cadmium plating |
| Insulator Material:     | CR-Elastomere                            |
| Contact Material:       | Copper alloy                             |
| Contact Plating:        | Hard silver                              |

| all dimensions are in mm   |   | drawing for             |
|--|---|-------------------------|
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  |   | CUSTOMER                |
| <br>ITT<br><i>Engineered for life</i><br>ITT CANNON GmbH<br>D-71336 Wiesenstedt/Germany | description   |                         |
|  | CA3100R24-22P-B-F80   |                         |
|  | Wall mounting receptacle<br>Shortened light-weight endbell without cable clamp<br>AWG Crimp / Pin / Layout: 24-22 |                         |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon                                     | page 1/1  | revision 392.12, Apr 11 |