



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 46.7 |
| B | 24.05 |
| C | 4 |
| D | 33.8 |
| E | 41.4 |
| F | 39.7 |
| G | 50.8 |
| H | M5 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification: | |
|-------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate over cadmium plating |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

| all dimensions are in mm | | drawing for | |
|---|---------------------------------------|--|--|
| Dimensions without tolerance indications are general tolerances in acc. with DIN 7168m | | CUSTOMER | |
| Engineered for life ITT CANADA GmbH © 1998 Wipac/Siemens | description | CA3102E28-21SWB-04 | |
| | | Box mounting receptacle (rear mount, threaded holes) | |
| | Metric Crimp / Socket / Layout: 28-21 | | |
| © All rights reserved. Reproduction or reuse in any form without written authorization of ITT Cannon. | page 1/1 | revision 392.12, Apr 11 | |