



NO.	BESCHREIBUNG / DESCRIPTION	
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET	
3	DICHTKÖRPER / GROMMET	
4	ENDRING / ENDRING	
6	KONTAKTBUCHSE / CONTACT SOCKET	
7	ZYLINDERGHÄUSE / BARREL	
9	ÜBERWURFMUTTER / COUPLING NUT	
14	F-ENDGEHÄUSE / F-ENDBELL	



NO.	MASSE / DIMENSIO			
А	40.5			
в	1 3/8-18NEF-2B			
с	19.8			
D	1 3/16-18NEF-2A			
Е	9.5			
F	58			



Note: Due to an automatic nomenclature system, numbers ge may not be sequential. Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
Notiz: Durch ein automatisches Benennungssystem können	Dimensions without tolerance indications are general tolerances in acc. with DIN7168m CUSTOMER
Nummerierungen entstehen, die nicht fortlaufend sind.	description CA3106F22-1S
Material Specification:	V ITT Plug, straight
Shell Material: Aluminium alloy	Endbell for flex tube
Shell Plating: Olive drab chromate coating over cadmium plating	Engineered for life
Insulator Material: Neoprene	TTT CONVOV Group D - 71384 Weinstad/Germany Solder Cup / Socket / Layout: 22-1
Contact Material: Copper alloy	© All rights reserved, Reproduction or issue to third in any form
Contact Plating: Hard silver	© All rights reserved, Reproduction or issue to third in any form whatever is only pennified with written authorization of ITT Cannon 1/1 evision 302 8. Feb 11
	· ·