


NO.	MASSE / DIMENSION
A	66.3
B	2 1/8-16N-2A
C	41


NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT / CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING



L-3609-P

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate over cadmium plating
Insulator Material:	CR-Elastomere
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN 7168m		drawing for CUSTOMER
 <b>ITT</b> Engineered for life <small>ITT CANON GmbH          D-72334 Weinstadt/Germany</small>	description CA3106E36-9P-B-F42	
	Plug, straight without Endbell Solder Cup / Pin / Layout: 36-9	
© All rights reserved. Reproduction or issue to third in any form whenever is only permitted with written authorization of ITT Canon	page 1/1	revision 392.12, Apr 11