



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 36.5 |
| B1 | 14.3 |
| B2 | - |
| C | 33 |
| D | 53 |
| E | 58 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 5 | KONTAKTSTIFT/ CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 12 | ENDGEHÄUSE / ENDBELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Note: Durch ein automatisches Benennungssystem können Nummernungen entstehen, die nicht fortlaufend sind.

| Material Specification: | |
|-------------------------|--------------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Zinc cobalt, black |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN71691

ITTT
 Engineered for Life
 ITT CONNECTOR
 ITT WIRELESS COMMUNICATIONS

description CA3108E18-19P-B-F80-A232
 Plug, 90°
 Endbell with clamp and bushing
 AWG Crimp / Pin / Layout: 18-19

© All rights reserved. Reproduction or use in third party files without the prior written authorization of ITT Connectors

page 1/1 revision 392 12 Apr 11

drawing for CUSTOMER