


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 50.2 |
| B | 1 3/4-18NS-2B |
| C | 1 7/16-18NEF-2A |
| D | 66 |
| E | 30.4 |
| F | 34 |
| G | 9.4 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3 | DICKTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 5 | KONTAKTSTIFT / CONTACT PIN |
| 7 | ZYLINDERGHÄUSE / BARREL |
| 9 | ÜBERWURFMUTTER / COUPLING NUT |
| 10 | DICHTRING FRONT / FRONT SEALING RING |
| 14 | F-ENDGEHÄUSE / F-ENDBELL |

| |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential. |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene |
| Contact Material: Copper alloy |
| Contact Plating: Hard silver |

| | | |
|---|--|---|
| all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | drawing for CUSTOMER |
|  ITT <i>Engineered for life</i> <small>ITT CANON GERMANY D-71284 Weinstadt-Germersheim</small> | description CA3108F28-15P Plug 90° Endbell for flex tube Solder Cup / Pin / Layout: 28-15 | |
| | <small>© All rights reserved. Reproduction or issue in any form without prior written authorization of ITT Canon</small> | <small>page 1/1</small> <small>revision 302.8, Feb 11</small> |