


| NO. | MASSE / DIMENSIO |
|-----|------------------|
| Α | 53.4 |
| В1 | 21.5 |
| B2 | 16.6 |
| С | 76 |

| NO. | BESCHREIBUNG / DESCRIPTION | |
|-----|---|--|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN DICHTKÖRPER / GROMMET | |
| 3 | | |
| 4 | ENDRING / ENDRING | |
| 5 | KONTAKTSTIFT/ CONTACT PIN | |
| 7 | ZYLINDERGHÄUSE / BARREL | |
| 9 | ÜBERWURFMUTTER / COUPLING NUT | |
| 10 | DICHTRING FRONT / FRONT SEALING RING | |
| 12 | ENDGEHÄUSE / ENDBELL | |



Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind

Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate over cadmium plating
Insulator Material: CR-Elastomere Contact Material: Copper alloy Contact Plating: Hard silver

all dimensions are in mm Dimensions without tolerance

drawing for CUSTOMER



CA3106E28-15PWB Plug, straight
Endbell with clamp and bushing
Solder Cup / Pin / Layout: 28-15

Engineered for life
ITT CANNON GmbH
D - 71384 Weinstadt/Germany

© All rights reserved. Reproduction or issue to third in any form page revision whatever is only permitted with written outhorization of ITT Compon 1/1/1 392 12. Apr 11

