



NO.	MASSE / DIMENSION
A	46.6
B	1 7/16-18UNE-F-2A
C	66
D	27.5
E	32
F	9.4

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING
14	F-ENDGEHÄUSE / F-ENDBELL

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate over cadmium plating
Insulator Material:	CR-Elastomere
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for CUSTOMER

**ITT**  
 Engineered for life  
 ITT CANADA GmbH  
 51-17384 Montreal/Canada

description CA3108F24-12P-B  
 Plug, 90°  
 Endbell for flex tube  
 Solder Cup / Pin / Layout: 24-12

© All rights reserved. Reproduction or issue in kind is only allowed with written authorization of ITT Cannon. page 1/1 revision 392.12, Apr 11