



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 40.9 |
| B | 27.6 |
| C | 23.05 |
| D | 4 |
| E | 54 |
| F | 34.9 |
| G | 44.5 |
| H | M4 |



| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTKÖRPER / GROMMET |
| 4 | ENDRING / ENDRING |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |
| 20 | KURZES ENDEGEHÄUSE/SHORT ENDBELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| | |
|-------------------------|--|
| Material Specification: | |
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate over cadmium plating |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

| | | |
|--|---|----------------|
| all dimensions are in mm | | drawing for |
| Dimensions without tolerance indications are general tolerances in acc. with DIN7168m | | CUSTOMER |
|  ITT Engineered for life <small>ITT CANNON GmbH D-71364 Weinstadt, Germany</small> | description | |
| | CA3100R24-10S-B-F80 Wall mounting receptacle Shortened light-weight endbell without cable clamp AWG Crimp / Socket / Layout: 24-10 | |
| © All rights reserved. Reproduction or issue to third in any form whoever is only permitted with written authorization of ITT Cannon | page | revision |
| | 1/1 | 392.12, Apr 11 |