





NO.	MASSE / DIMENSION
А	53.4
В1	21.5
B2	16.6
С	43.3
D	58
Е	66

NO.	BESCHREIBUNG / DESCRIPTION			
1	ISOLIERKÖRPER STIFT / INSULATOR PIN			
3	DICHTKÖRPER / GROMMET			
4	ENDRING / ENDRING			
5	KONTAKTSTIFT/ CONTACT PIN			
7	ZYLINDERGHÄUSE / BARREL			
9	ÜBERWURFMUTTER / COUPLING NUT			
10	DICHTRING FRONT / FRONT SEALING RING			
12	ENDGEHÄUSE / ENDBELL			

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.		all disensions are in an Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for
Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.				CUSTOMER
nummenerungen entstenen, die nicht fortlaufend sind.	-	 🚴	description CA3108F28-15PV	VB
Material Specification:		V ITT	Plug, 90°	
Shell Material: Aluminium alloy	7			
Shell Plating: Olive drab chromate over cadmium plating	7	Engineered for life	Endbell with clamp and bushing	
Insulator Material: CR-Elastomere	7	ITT CANNON GmbN D - 71384 Weinstadt/Germany	Solder Cup / Pin / Layout: 28-15	
Contact Material: Copper alloy		© All rights reserved, Regroduction or issue to third in any form undoewer is only penalted with written outhorization of ITT Common 1/1/1 392 1.2. Apr 1.1		sion
Contact Plating: Hard silver				12. Apr 11