

**VIP-CAB-FLK16/FR/OE/0,14/2,0M**

Order No.: 2900133

The figure shows the 14-pos. version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2900133>

Assembled round cable with a 16-pos. molded socket strip (90° output) and an open end. On the open end, the wires are labeled with 1 to 16 and have ferrules, cable length: 2 m

**Commercial data**

GTIN (EAN)	4046356476881
sales group	I580
Pack	1 pcs.
Customs tariff	85444290
Weight/Piece	0.1536 KG
Catalog page information	Page 260 (IF-2009)

**Product notes**WEEE/RoHS-compliant since:  
04/01/2009

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General**

Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 $\Omega$ /m

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	16
Number of connectors, control side	0
Number of connectors, modul side	1
Fixed cable length	2 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.5 mm
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding	no

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;