

☐ G ±0.3	
☐ G ±0.3 ☐ F ±0.1 ☐ 1.65 _0.25 ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	_
Н	

NO.	MASSE / DIMENSIO
Α	1 3/4-18NS-2A
В	20.6
С	4
D	34.2
Е	41.2
F	39.7
G	50.8
H	3.7

NO.	BESCHREIBUNG / DESCRIPTION			
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET			
6	KONTAKTBUCHSE / CONTACT SOCKET			
8	DOSENGEHÄUSE / SHELL			



	Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	1	all dimensions are in mm	drawing for
	Notiz: Durch ein automatisches Benennungssystem können	1	Dimensions without tolerance indi	ications are general tolerances in acc. with DIN7168m CUSTOMER
	Nummerierungen entstehen, die nicht fortlaufend sind.	J	│ 	description CA3102E28-10S
	Material Specification:		V ITT	Box mounting receptacle
	Shell Material: Aluminium alloy	1		Dox mounting receptable
	Shell Plating: Olive drab chromate coating over cadmium plati	plating Engineered for	Engineered for life	Caldas Co. / Castast / Laurent 20 40
	Insulator Material: Neoprene]	ITT CANNON GrapH D - 71384 Weinstadt/Germany	Solder Cup / Socket / Layout: 28-10
	Contact Material: Copper alloy		© All rights reserved. Reproduction or	
Contact Plating: Hard silver			wholever is only permitted with written or	utherization of ITT Common 1/1 1/1 302 8, Feb 11