



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 60.1              |
| B1  | 26.8              |
| B2  | 21.5              |
| C   | 51.7              |
| D   | 66                |
| E   | 72                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICHTKÖRPER / GROMMET                |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT/ CONTACT PIN            |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 12  | ENDGEHÄUSE / ENDBELL                 |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Note: Durch ein automatisches Benennungssystem können Nummernungen entstehen, die nicht fortlaufend sind.

| Material Specification:                                 |
|---|
| Shell Material: Aluminium alloy                         |
| Shell Plating: Olive drab chromate over cadmium plating |
| Insulator Material: CR-Elastomere                       |
| Contact Material: Copper alloy                          |
| Contact Plating: Hard silver                            |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN71691

drawing for CUSTOMER

|   |   |
|---|---|
| <br><b>ITT</b><br><i>Engineered for Life</i><br><small>ITT PACIFIC CORP.</small><br><small>5710 Woodloch Drive</small> | description CA3108E32-1P-B-01<br>Plug, 90°<br>Endbell with clamp and bushing<br>Metric Crimp / Pin / Layout: 32-1 |
|   | page 1/1<br>revision 392 12, Apr 11   |

All rights reserved. Reproduction or use in third party files without the written authorization of ITT Connect.