



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 60.1              |
| B   | 32.5              |
| C   | 1 3/4-18UNS-2A    |
| D   | 11                |
| E   | 62                |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 7   | ZYLINDERGHÄUSE / BARREL             |
| 9   | ÜBERWURFMUTTER / COUPLING NUT       |
| 10  | DICHRING FRONT / FRONT SEALING RING |
| 14  | F-ENDGEHÄUSE / F-ENDBELL            |



|  |
|--|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.                      |
| Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind. |
| Material Specification:  |
| Shell Material: Aluminium alloy  |
| Shell Plating: Olive drab chromate over cadmium plating  |
| Insulator Material: CR-Elastomere  |
| Contact Material: Copper alloy   |
| Contact Plating: Hard silver   |

|   |  |
|---|--|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m   | drawing for<br>CUSTOMER  |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT Cannon GmbH<br/>D-71334 Wernau, Germany</small> | description CA3106F32-1P-B<br>Plug, straight<br>Endbell for flex tube<br>Solder Cup / Pin / Layout: 32-1 |
| <small>© All rights reserved. Reproduction or issue to third in any form<br/>whenever is only permitted with written authorization of ITT Cannon</small>  | page 1/1<br>revision 392 12, Apr 11  |