


_	2 ±0.25
	1

NO.	MASSE / DIMENSIO
А	53.4
В	27
С	1 7/16-18UNEF-2A
D	9.5
Е	60

NO. BESCHREIBUNG / DES		BESCHREIBUNG / DESCRIPTION	
	2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET	
3 DICHTKÖRPER / GROMMET		DICHTKÖRPER / GROMMET	
	4	4 ENDRING / ENDRING	
	6	KONTAKTBUCHSE / CONTACT SOCKET	
	7	ZYLINDERGHÄUSE / BARREL	
	9 ÜBERWURFMUTTER / COUPLING NUT		
10 DICHTRING FRONT / FRONT SEALING RING		DICHTRING FRONT / FRONT SEALING RING	
	14	F-ENDGEHÄUSE / F-ENDBELL	



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm drawing for	
Notiz: Durch ein automatisches Benennungssystem können	Dimensions without tolerance indications are general tolerances in acc. with DIN7168m CUSTOMER	
Nummerierungen entstehen, die nicht fortlaufend sind.	description CA3106F28-15S-B-01	
Material Specification:	Plug, straight	
Shell Material: Aluminium alloy	Endbell for flex tube	
Shell Plating: Olive drab chromate over cadmium plating	Engineered for life	
Insulator Material: CR-Elastomere	ITT CANNON Gribt D - 71384 Weinstadt/Germany Metric Crimp / Socket / Layout: 28-15	
Contact Material: Copper alloy	© All rights reserved. Reproduction or issue to third in any form page revision whatever is andy permitted with written authorization of ITT Cornon	
Contact Plating: Hard silver	wholever is only permitted with written authorization of ITT Cannon 1/1/1 392 12. Apr 11	