


| NO. | MASSE / DIMENSIO |
|-----|------------------|
| A   | 60.1             |
| B1  | 26.8             |
| B2  | 21.5             |
| C   | 76               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHTRING FRONT / FRONT SEALING RING    |
| 12  | ENDGEHÄUSE / ENDBELL                    |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

| Material Specification: |  |
|-------------------------|--|
| Shell Material:         | Aluminium alloy                          |
| Shell Plating:          | Olive drab chromate over cadmium plating |
| Insulator Material:     | CR-Elastomere                            |
| Contact Material:       | Copper alloy                             |
| Contact Plating:        | Hard silver                              |

| all dimensions are in mm  |  | drawing for |                         |
|---|--|-------------|-------------------------|
| Dimensions without tolerance indications are general tolerances in acc. with DIN7188m   |  | CUSTOMER    |                         |
| <br>Enginedered for life<br>ITT CANNON GmbH<br>D-73844 Nürting/Germany | description CA3106E32-7S-B   |             |                         |
|   | Plug, straight   |             |                         |
|   | Endbell with clamp and bushing<br>Solder Cup / Socket / Layout: 32-7 |             |                         |
| © All rights reserved. Reproduction or issue to third in any form<br>whenever is only permitted with written authorization of ITT Cannon                    |  | page 1/1    | revision 392.12, Apr 11 |