


NO.	MASSE / DIMENSION
A	43.1
B	1 3/16-18UNEF-2A
C	61
D	24.6
E	30
F	9.4

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICKTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING
11	SCHIRMKRANZ/SHIELDING BRAID
14	F-ENDGEHÄUSE / F-ENDBELL

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate over cadmium plating
Insulator Material:	CR-Elastomere
Contact Material:	Copper alloy
Contact Plating:	Hard silver

<b>all dimensions are in mm</b> <small>Dimensions without tolerance indications are general tolerances in acc. with DIN 7168m</small>		drawing for <b>CUSTOMER</b>
 <b>ITT</b> <small>Engineered for life</small> <small>ITT CONNECTOR GROUP</small> <small>© 1998 WehrstedtGermany</small>	description: CA3108F22-22P-B-14 Plug, 90° shielded Endbell for flex tube Metric Crimp / Pin / Layout: 22-22	
	<small>© All rights reserved. Reproduction or use in any form without the written authorization of ITT Connectors is only permitted with written authorization of ITT Connectors.</small>	page 1/1 revision 392.12, Apr 11