



NO.	MASSE / DIMENSION
A	43.1
B	1 3/16-18UNEF-2A
C	61
D	24.6
E	30
F	9.4

NO.	BESCHREIBUNG / DESCRIPTION
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET
3	DICKTKÖRPER / GROMMET
4	ENDRING / ENDRING
6	KONTAKTBUCHSE / CONTACT SOCKET
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
10	DICHTRING FRONT / FRONT SEALING RING
11	SCHIRMKRANZ / SHIELDING BRAID
14	F-ENDGEHÄUSE / F-ENDBELL

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate over cadmium plating
Insulator Material: CR-Elastomere
Contact Material: Copper alloy
Contact Plating: Hard silver

<p>all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7180m</p> <p>ITT Engineered for life ITT CONNECTOR GROUP 21738 Haverhill, Germany</p> <p>© All rights reserved. Reproduction or issue to third in any form without prior written authorization of ITT Connectors is only permitted with written authorization of ITT Connectors.</p>	<p>description CA3108F22-22S-B-14 Plug, 90° shielded Endbell for flex tube Metric Crimp / Socket / Layout: 22-22</p> <p>page 1/1 revision 382.12, Apr 11</p>	<p>drawing for CUSTOMER</p>
---	--	-----------------------------