



	NO.	BESCHREIBUNG / DESCRIPTION
	1	ISOLIERKÖRPER STIFT / INSULATOR PIN
	3	DICHTKÖRPER / GROMMET
	4	ENDRING / ENDRING
-	5	KONTAKTSTIFT/ CONTACT PIN
	8	DOSENGEHÄUSE / SHELL
	20	KURZES ENDGEHÄUSE/SHORT ENDBELL



NO.	MASSE / DIMENSIO
А	2-18NS-2A
в	38.5
с	22.2
D	3.2
E	53
F	44.5
G	57
н	4.4



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.	all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for
Notiz: Durch ein automatisches Benennungssystem können			CUSTOMER
Nummerierungen entstehen, die nicht fortlaufend sind.	8 A A A A A A A A A A A A A A A A A A A	description CA3100R32-1P	
Material Specification:	🗆 💙 ІТТ	Vall mounting receptacle	
Shell Material: Aluminium alloy		0 1	and apple slaves
Shell Plating: Olive drab chromate coating over cadmium plating	Engineered for life ITT CANNON GmbH D - 71384 Weinstadt/Germany	Shortened light-weight endbell without cable clamp Solder Cup / Pin / Layout: 32-1	
Insulator Material: Neoprene			
Contact Material: Copper alloy	© All rights reserved. Reproduction or is	ssue to third in any form the page revisi	ion
Contact Plating: Hard silver	whotever is only permitted with written out	3. Feb 11	