

# SACC-CI-M12FS-5CON-L180-THR


Order No.: 1551448



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1551448>

Sensor/actuator flush-type socket, 5-pos., A-coded, with straight THR solder connection, only contact insert

## Commercial data

GTIN (EAN)	 4 046356 153683
sales group	D125
Pack	60 pcs.
Customs tariff	85366990
Catalog page information	Page 33 (PC-2009)

## Product notes

WEEE/RoHS-compliant since:  
04/13/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data


Rated current at 40°C	4 A
Rated voltage	60 V
Number of positions	5
Volume resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ

Ambient temperature (operation)	-25 °C ... 85 °C (Male connector / female connector)
<b>General characteristics</b>	
Standards/regulations	M12 connector IEC 61076-2-101
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 66
Sealing material	FKM / EPDM
Mounting type	PCB mounting
Type of connection	THR solder connection
Status display	No


#### Diagrams/Drawings

##### Drilling plan/solder pad geometry


Drilling diagram



##### Dimensioned drawing




M12 female connector contact carrier



THR tray packaging

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;