


SACC-M 8MS-4QO-0,25-M

Order No.: 1441011



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1441011>

Sensor/actuator connector, male connector, straight, 4-pos., M8, QUICKON-ONE, metal knurl, maximum cable diameter of 5.0 mm

Commercial data	
GTIN (EAN)	 4 046356 515900
sales group	D120
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 113 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
06/16/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Rated current at 40°C	4 A
Rated voltage	30 V
Number of positions	4
Volume resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ

Ambient temperature (operation)	-25 °C ... 80 °C (Male connector / female connector)
---------------------------------	--

General characteristics

Standards/regulations	M8 connector IEC 61076-2-104
Coding	A - standard
Surge voltage category	II
Pollution degree	3
Degree of protection	IP65/67
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU
Material of grip body	PA 6
Material, knurls	Nickel-plated brass
Type of connection	QUICKON fast connection
Conductor cross section stranded min.	0.08 mm ²
Conductor cross section stranded max.	0.25 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	24
Frequency of connections between conductors of the same cross section	10
External cable diameter	2.5 mm ... 5 mm +/-0.2 mm
Wire insulation material	PVC/PE/PP
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	Class 2-6
Status display	No


Diagrams/Drawings

Dimensioned drawing

M8 x 1 male connector, straight version

Schematic diagram

Pin assignment M8 plug, 4-pos., view male side



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;