



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 53.4              |
| B   | 24.05             |
| C   | 4                 |
| D   | 33.8              |
| E   | 47.8              |
| F   | 44.5              |
| G   | 57                |
| H   | 4.3               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

|                         |  |
|-------------------------|--|
| Material Specification: |  |
| Shell Material:         | Aluminium alloy                          |
| Shell Plating:          | Olive drab chromate over cadmium plating |
| Insulator Material:     | CR-Elastomere                            |
| Contact Material:       | Copper alloy                             |
| Contact Plating:        | Hard silver                              |

|  |   |                         |
|--|---|-------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m      |   | drawing for<br>CUSTOMER |
| <br><b>ITT</b><br><i>Engineered for life</i><br><small>ITT ELECTRONICS GmbH<br/>       01738B Hannover Germany</small> | description   | CA3102E32-8S-B-05       |
|  | Box mounting receptacle (rear mount, through holes) |                         |
| Solder Cup / Socket / Layout: 32-8   |   |                         |
| © All rights reserved. Reproduction or issue to third in any form without prior written authorization of ITT Cannon    | page 1/1  | revision 382.12, Apr 11 |