


GKDS

Order No.: 1706028

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1706028>

PC terminal block, Nominal current: 24 A, Nom. voltage: 500 V,
Pitch: 7.5 mm, Number of positions: 1, Type of connection: Screw
connection, Mounting: Soldering, Conductor/PCB connection direction:
0 °, Color: green, The article can be aligned to create different nos. of
positions!

Commercial data

GTIN (EAN)	 4 017918 023324
sales group	E051
Pack	50 pcs.
Customs tariff	85369010

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CCA, CSA, LR, RS, SEV, UL

Accessories

Item	Designation	Description
Assembly		
1701793	TP-KDS/GKDS	PCB terminal block
Bridges		
0801157	EB 2- BK 4	Insertion bridge, 2-pos., for strip terminal block, BK 4
0801144	EB 3- BK 4	Insertion bridge, 3-pos., for strip terminal block, BK 4
0801131	EB 10- BK 4	Insertion bridge, 10-pos., for strip terminal block, BK 4
General		
1706057	GRZ 2,5	
Marking		
1051993	B-STIFT	Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm
1401844	BN-ZB 7,5/WH:UNBEDRUCKT	BN Zack strip, unprinted: 10-section, for individual labeling with M-PEN or CMS system, sufficient for labeling 100 terminal blocks
Plug/Adapter		
0201744	MPS-MT	Test plugs
0201647	RPS	Reducing plug, Color: gray
Tools		
1205053	SZS 0,6X3,5	Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;