


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF20292-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1820 @ 0°C	810	5	38,000 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
				TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>					
<b>A</b> DIMENSION CHANGES RELEASED		12/19/02 2/28/02	DRAWN BY L. WENGSTROM	APPV'D BY DATE F.D. 12/19/02	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF20292-24B</b>		
REV. NO. DESCRIPTION/ECO NUMBER		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	RELEASED DATE 2/28/02	REVISION DATE 12/19/02	REV. NO. <b>A</b>	SHEET 1 OF 1