



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF3222-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1100 @ 0°C	440	5 ± 1	28,000 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	<b>COMPONENTS CORPORATION</b>			
	THIRD ANGLE PROJECTION DRAWN BY L. WENGSTROM APP'VD BY DATE FD 8/20/02	TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>		SIZE <b>A</b> SCALE NONE	FSCM NO. <b>55335</b> DRAWING NO. <b>BF3222-24B</b>
REV. NO. [ ] DESCRIPTION/ECO NUMBER [ ] APP'VD DATE [ ]	<b>- CAD DRAWING -</b> MANUAL REVISIONS NOT PERMITTED		RELEASED DATE <b>8/20/02</b>	REVISION DATE [ ]	REV. NO. [ ] SHEET <b>1 of 1</b>