



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26240-24B	LCD HIGH OUTPUT WHITE 11000°k RGB	1250 @ 0°C	505	5	30,000 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENSIONS ARE IN MILLIMETERS		<b>JKL COMPONENTS CORPORATION</b>						
				TOLERANCE UNLESS OTHERWISE SPECIFIED							TITLE	
			THIRD ANGLE PROJECTION	1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		MINIATURE COLD CATHODE FLUORESCENT LAMP						
A			DIM LINE CORRECT. AND 240+/-5.0 TO 240+/-3.0	10/17/00	DRAWN BY	APPVD BY	DATE	SIZE	FSCM NO.	DRAWING NO.	BF26240-24B	
RELEASED				5/22/00	L. WENGSTROM	FD	10/17/00	A	55335			
REV. NO.	DESCRIPTION/ECO NUMBER		APPVD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
								NONE	5/22/00	10/17/00	A	1 OF 1