


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF26318-20B	LCD HIGH OUTPUT WHITE 5300°k RGB	1636 @ 0°C	676	5	34,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
			DRAWN BY L. WENGSTROM		APPV'D BY DATE F.D. 2/28/02		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		DRAWING NO. BF26318-20B	
RELEASED			2/28/02		SIZE A		FSCM NO. 55335		SCALE NONE	
REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE			APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		RELEASED DATE 2/28/02		REVISION DATE REV. NO. SHEET 1 OF 1	